

**GENERAL SPECIFICATIONS**

Bore diameter:	29mm (1.1")
Total length:	50 cm (20")
Total weight:	2.6 kg (5.7 lbs.)
Height on stand:	52.5 cm (21") maximum
Composition:	Titanium, Stainless Steel and Aluminium
Ignition voltage:	P-Series Blasting Machine; 24 volts; 1 amp
Laser system:	29mm Dual Laser Pointer Assembly
Liquid projectile:	190 mL (6.4 oz.)
Liquid load:	190 mL (6.4 oz.)
Peak liquid projectile velocity:	465 m/s (1,525 ft/s)
Kinetic energy:	15.2 kJ
Recoil impulse:	88.4 N.s
Vertical adjustment:	180°
Horizontal adjustment:	360°, for multi-purpose positioning
Barrel composition:	Titanium
Barrel length:	38 cm (15")
Barrel weight:	1.8 kg (4.0 lbs.)

Product specifications and images are subject to change without notice.

DESCRIPTION

The 29mm Neutrex disrupter, is also available in a reduced weight titanium option. The disrupter is capable of disarming IED packages of approximately 16 kg (35 lbs.). A gas cylinder recoil system, reducing recoil by 30%, is incorporated into the barrel clamp assembly which enables the disrupter to be robot mounted. The disrupter with stand, may be hand carried for manual deployment. Setup and preparation time is approximately 2 ½ minutes. Maximum recommended standoff is 5 metres (15 ft.) dependent on target.

AMMUNITION

- A - Electrically primed - 105 grain
- B - Electrically primed - 25 grain
- C - 29mm Avon Frangible
- D - 29mm Flathead Steel Slug
- E - Gel Shot

Ammunition is not included as part of the system.


Warranty valid only with the use of Proparms ammunition.



A B C D

ACCESSORIES

P2 Blasting Machine



Wire Wheel
100 m (330 ft)



Bore Laser Kit



Universal
Knapsack